






# 315DZ

AGG. 11/20

3~ 50 Hz. 400V	
<b>DEUTZ</b>	
EU STAGE 2	
69 db(A) @ 7 mt	
400 lt	

PRIME POWER		STAND-BY POWER	
kVA	kW	kVA	kW
<b>315</b>	<b>252</b>	<b>346,5</b>	<b>277,2</b>

ENVIRONMENTAL CONDITIONS	
Temperature	<b>40° C</b>
Height	<b>1000 mslm</b>
Humidity	<b>60%</b>

**OPEN VERSION B400**

**SOUNDPROOF VERSION C450**


The image is only for demonstration purposes

WEIGHT	DIMENSIONS		
	L [mm]	W [mm]	H [mm]
kg			
<b>2825</b>	<b>2950</b>	<b>1550</b>	<b>2100</b>

WEIGHT	DIMENSIONS		
	L [mm]	W [mm]	H [mm]
kg			
<b>3815</b>	<b>4300</b>	<b>1750</b>	<b>2350</b>

## TECHNICAL DETAILS

<b>ELECTRICAL DATA</b>	Electrical system type	3F+N	~
	Power factor	0,8	φ
	Voltage	400	V
	Frequency	50	Hz
	PRP Ampere rating	454,6	A
<b>ENGINE</b>	Engine	DEUTZ BF6M 1015 C G1	
	Engine emissions standard (REG. UE 2016/1628)	EU STAGE 2	
	RPM governor	Mechanical	
	Performance class (ISO8528-5)	G2	
	Rpm	1500	rpm
	Nr. of cylinders	6	
	Bore x stroke	132 x 145	mm
	Displacement	11906	cc
	Induction system	Turbocharged	
	Cooling system	Water	
	Engine net prime power	363,3 (271)	Hp (kW)
Exhaust gas aftertreatment	/		
<b>CONSUMPTION</b>	Fuel type	Diesel	
	Consumption @ 50-75-100% load	27 -41 - 56	lt/h
	Standard tank capacity	400	lt
	Autonomy @ 75% load	9,8	h
<b>ALTERNATOR</b>	Alternator	Sovralimentata – MECCALTE – MARELLI MOTORI	
	Type	Self excited, brushless	
	Number of poles	4	
	Insulation class	H	
	Temperature rise class	H	
	Voltage regulation	AVR	
	Voltage precision	± 1	%
<b>GENERAL</b>	Sound level (soundproof version)	69	dB(A) 7mt
	Exhaust pipe diameter	200	mm
	Electrical system voltage	24	V

## ELECTRIC PANEL

### MANUAL

### AUTOMATIC MAINS FAILURE



Electronic control unit with multimeter	<b>COMAP AMF25</b>	<b>COMAP AMF25</b>
Electrical panel enclosure protection degree	<b>IP44</b>	
ON-OFF electric panel switch	<i>Key type</i>	<i>Without key</i>
Emergency pushbutton	<b>STANDARD</b>	
Battery charge maintainer	/	<b>24V 5A</b>
Power supply	<i>Full power terminal</i>	<i>Full power terminal</i>
Circuit breaker	<i>Magneto thermal type 4P ABB Tmax-XT 630A</i>	<i>Magneto thermal type 4P ABB Tmax-XT 630A</i>
Main protection alarms	<i>Min-max V and Hz. LOP. HWT. Battery charger alternator failure. Low fuel level</i>	

## STANDARD ELECTRONIC CONTROL UNIT

COMAP  
AMF25



*Functions: automatic or manual start, remote start, periodic test*

*Multimeter V (L1, L2, L3, N), A (L1, L2, L3), Hz, kVA, battery V, hour counter*

*Backlit LCD display. USB port*

*Communication accessories available: Ethernet, GSM-GPRS, 4G, GPS*


## OPTIONAL ELECTRONIC CONTROL UNIT



DEEP SEA DSE7320 MKII

**SOUNDPROOF AND WEATHERPROOF CANOPY**



<i>Self-supporting frame material</i>	<i>Carbon steel sheet, electro-welded, minimum thickness 4 mm</i>
<i>Soundproof canopy material</i>	<i>Carbon steel sheet, electro-welded, thickness between 2 and 9 mm</i>
<i>Painting</i>	<i>Epoxy powder RAL 5015 textured, outdoor-proof</i>
<i>In-built fuel tank</i>	<b>400 lt+</b> Drip tray
<i>Soundproofing coating material</i>	<i>Polyester fiber. Fire resistance EN13501-1 class B</i>
<i>Muffler</i>	<i>In-built the canopy. Residential type with sound reduction 35 dB(A)</i>
<i>Access openings</i>	<i>n.4 doors with padlockable key lock</i>
<i>Electric panel</i>	<i>Lateral side position. Dedicated door with key lock</i>
<i>Fresh air intake and hot air expulsion</i>	
<i>Lifting system</i>	<i>n.4 lifting hooks</i>
<i>Support feet</i>	<i>n.4 support feet with holes for machine ground fastening</i>

## MAIN OPTIONS



630A automatic transfer switch (ATS)



600 lt bigger fuel tank with drip tray



2250W engine preheating system



Automatic fuel transfer kit with manual by-pass system



Residual current protection relay adjustable in sensitivity and intervention time.

## OTHER OPTIONS

Power distribution socket set  
Synchronizing electric panel  
Battery switch  
Remote control systems **ETHERNET, 2G - 3G - 4G, GPS**

Further alternator brand  
Quick couplings for connecting an external tank with three way valve  
Outdoor, underground and transportable tanks -  
Slow or fast towing trailer  
Front hot air expulsion canopy  
Further colors

Greenpower AB  
Helsingborgsvägen Varalöv,  
262 96 Ängelholm, Sweden  
Phone: +46 43122240  
Email: [info@greenpower.se](mailto:info@greenpower.se)  
Web: [www.greenpower.se](http://www.greenpower.se)