

INDUSTRIAL SERIES

V18Y

AGG. 12/20

PRIME POWER		STAND-BY POWER	
kVA	kW	kVA	kW
18	14,4	19,8	15,8

ENVIRONMENTAL CONDITIONS	
Temperature	40° C
Height	1000 mslm
Humidity	60%

3~ 50 Hz. 400V	
YANMAR	
EU STAGE 5	
69 dB(A) @ 7 mt	
100 lt	

OPEN VERSION B20

SOUNDPROOF VERSION C30



The image is only for demonstration purposes

WEIGHT	DIMENSIONS		
kg	L [mm]	W [mm]	H [mm]
460	1400	700	1400

WEIGHT	DIMENSIONS		
kg	L [mm]	W [mm]	H [mm]
635	1800	850	1275

TECHNICAL DETAILS

ELECTRICAL DATA	Electrical system type	3F+N	~
	Power factor	0,8	φ
	Voltage	400	V
	Frequency	50	Hz
	PRP Ampere rating	26	A
ENGINE	Engine	YANMAR 4TNV88-BIB	
	Engine emissions standard (REG. UE 2016/1628)	EU STAGE 5	
	RPM governor	Mechanical	
	Performance class (ISO8528-5)	G2	
	Rpm	1500	rpm
	Nr. of cylinders	4	
	Bore x stroke	88 x 90	mm
	Displacement	2190	cc
	Induction system	Natural	
	Cooling system	Water	
	Engine net prime power	22,4 (16,7)	Hp (kW)
	Exhaust gas aftertreatment	/	
CONSUMPTION	Fuel type	Diesel	
	Consumption @ 50-75-100% carico – load - charge	/ – 4 – /	lt/h
	Standard tank capacity	100	lt
	Autonomy @ 75% carico – load - charge	25	h
ALTERNATOR	Alternator	LINZ ELECTRIC – STAMFORD – MECC ALTE	
	Type	Self excited, brushless	
	Number of poles	4	
	Insulation class	H	
	Temperature rise class	H	
	Voltage regulation	AVR	
	Voltage precision	± 1	%
GENERAL	Sound level (soundproof version)	69	dB(A) 7mt
	Exhaust pipe diameter	60	mm
	Electrical system voltage	12	V

ELECTRIC PANEL

MANUAL

AUTOMATIC MAINS FAILURE



Electronic control unit with multimeter	LOVATO ELECTRIC RGK420SA	COMAP IntelliLite 9
Electrical panel enclosure protection degree	IP44	
ON-OFF electric panel switch	Key type. In-built the control unit	Without key
Emergency pushbutton	STANDARD	
Battery charge maintainer	/	12V 3A
Power supply	ECC IP67 sockets: n.1 3P 16A + n.1 5P 32A	Full power terminal
Circuit breaker	Magnetothermal type 1P+N 16A and 4P 32A	Magnetothermal type 4P 32A
Main protection alarms	Min-max V and Hz. LOP. HWT. Battery charger alternator failure. Low fuel level	

STANDARD ELECTRONIC CONTROL UNIT

LOVATO ELECTRIC
RGK420 SA



Functions: manual start, remote start, periodic test

Multimeter V (L1, L2, L3, N), A (L1), Hz, kVA, battery V, hour counter

Backlit LCD display. Optical port and NFC

COMAP
IntelliLite 9



Functions: automatic or manual start, remote start, periodic test

Multimeter V (L1, L2, L3, N), A (L1, L2, L3), Hz, kVA, battery V, hour counter

Backlit LCD display. USB port

Communication accessories available: Ethernet, GSM-GPRS, 4G, GPS

OPTIONAL ELECTRONIC CONTROL UNIT




DEEP SEA DSE4520 MKII
DEEP SEA DSE7320 MKII



COMAP AMF25

SOUNDPROOF AND WEATHERPROOF CANOPY



Self-supporting frame material	Carbon steel sheet, electro-welded, minimum thickness 2,5 mm
Soundproof canopy material	Carbon steel sheet, electro-welded, thickness between 1,5 and 4,5 mm
Painting	Epoxy powder RAL 5015 textured, outdoor-proof
In-built fuel tank	100 lt + Drip tray
Soundproofing coating material	Polyurethane finished with water-repellent and anti-oil fabric. Fire resistance EN13501-1 class B
Muffler	In-built the canopy. Residential type with sound reduction 35 dB(A)
Access openings	n.2 doors with key lock
Electric panel	Short side position. Dedicated protective door with padlockable lock and porthole (only GS with automatic panel)
Fresh air intake and hot air expulsion	
Lifting system	n.4 lifting hooks
Support feet	n.4 support feet with holes for machine ground fastening

CONTAINER TRANSPORTABILITY ADVANTAGES

VERSION	20' BOX	40' BOX	40' HC
	6	13	13
N. transportable pieces			
	6	13	26

MAIN OPTIONS



32A automatic transfer switch (ATS)



200 lt bigger fuel tank with drip tray



750W engine preheating system



Automatic fuel transfer kit with manual by-pass system



Residual current circuit breaker



Electric fuel float to check the fuel level from the electronic control unit



Engine oil pressure and cooling water temperature measuring instruments

OTHER OPTIONS

Power distribution socket set

Synchronizing electric panel

Battery switch

*Remote control systems **ETHERNET, 2G - 3G - 4G, GPS***

Further alternator brand

Quick couplings for connecting an external tank with three way valve

Outdoor, underground and transportable tanks

Slow or fast towing trailer

Front hot air expulsion canopy

Further colors

VERSIONS WITH SPECIAL EQUIPMENT



RENTAL

Special version with features designed for the rental market



ZERO NOISE

Super sound-proofed special version, noise level 50, 55 or 60 dB(A)

STANDARD FEATURES

	≤50 kVA	80 kVA	120 kVA	200 kVA	275 kVA	≥550 kVA		
Mechanical fuel gauge	STANDARD	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL		
Electric fuel gauge	OPTIONAL	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD		
Coolant temperature and oil pressure allarm	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD		
Coolant temperature and oil pressure measuring sensor	OPTIONAL	OPTIONAL	STANDARD	STANDARD	STANDARD	STANDARD		
Oil sump pump	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	STANDARD	STANDARD		
110% containment basin	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD		
Noise level compliant to 2000/14/CE	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD	STANDARD		
Galvanized steel mode canopy	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL	OPTIONAL		
	C20	C30	C50	C100	C200	C300	C450	≥C500

OPTIONS

| OTHER OPTIONS |

30A ATS panel (mains-genset)

Bigger fuel tank [200lt - 300lt] with drip tray

Engine preheat heater for starting in harsh climate conditions [750W]

Automatic fuel transfer kit with manual bypass system

Power distribution panel with 4/6 EEC sockets

Quick couplings for connecting an external tank with three way valve

Remote monitoring and control systems (Ethernet, 4G, GPS)

| OTHER OPTIONS |

Master battery switch

Parallel framework between groups or between groups and network

Cab with front/side air intake and/or exhaust

Outdoor, underground and trasportable tanks

Slow or fast towing trailer

Further colors

