

GP5000E

GP5000E series gasoline generating sets, 3000 rpm, sturdy and easy to handle, specially designed for professionals and yards. These generating sets have been designed with dedicated electrical panel with residual current protection and oversized protective rainproof cover. 3000 rpm gensets have been designed for stand-by use only. Not recommended using for more than 6 hours continuously or more than 500 hours/year.



PRIME POWER		STAND-BY POWER	
-------------	--	----------------	--

kVA	kW	kVA	kW
5	4,5	5,5	4,95


WEIGHT	DIMENSIONS		
--------	------------	--	--

kg	L [mm]	W [mm]	H [mm]
78	825	550	530

TECHNICAL DETAILS

ELECTRICAL DATA	Electrical system type	1F+N	~
	Power factor	0,9	φ
	Voltage	230	V
	Frequency	50	Hz
	Ampere rating	24	A
ENGINE DATA	Engine	HONDA GX270	
	Engine emissions standards	STAGE V	
	Engine power	6,2 (4,6)	Hp (kW)
	Rpm	3000	
	Nr. of cylinders	1	
	Engine starting system	Electric starter	
	Displacement	270	cc
FUEL CONSUMPTION DATA	Fuel type	Petrol	
	Consumption	1,6	liter/time @ 75%
	Tank capacity	15	liter/time
	Autonomy	9,4	h
ALTERNATOR DATA	Alternator	LINZ ELECTRIC – NSM	
	Type	Self-excited, with brushes	
	Voltage regulation	AVR	
	Voltage precision	± 2	%

STANDARD EQUIPMENT



Steel base frame, epoxy powder painted



Bigger fuel tank for greater



autonomy Ant-vibration dampers



First filling liquids



Electric starting with 12V battery



Automatic voltage regulator (AVR)



Electric manual panel with multimeter and hour counter:
-n.1 schuko and n.1 230V 16A 3P + n.1 230V 32A 3P ECC sockets
-12VDC socket. MCB with residual current protection



Slow trolley for manual handling



Automatic mains failure panel
-With integrated automatic transfer switch and battery charger



Greenpower AB

Helsingborgsvägen Varalöv
262 96 Ängelholm
Tel: 0431-222 40
E-mail: info@greenpower.se
web: www.greenpower.se